

Certifications & Standards:

Tested & Certified to ASTM C 1461
 Tested & Certified to ASTM C 1440
 IAPMO File 3251

Material Specifications:

Clamp: Type 301 AISI stainless steel
Screw: Type 301 AISI stainless steel
Gasket: (Santoprene) 101-87

Rigid Quik Slip-On Couplings:

The Rigid Quik Slip-On Coupling joins various types of piping materials and diameters for a drain, waste and vent (DWV) system.

Simplified Design:

Rigid Santoprene gaskets eliminate the need for stainless steel shields. The Rigid Quik Slip-On Coupling DOES NOT require disassembly prior to assembly of the joint.

The Rigid Quik Slip-On Coupling DOES NOT require the gasket to be stretched over the pipe or fitting.

Installation Benefits:

The Rigid Quik Slip-On Coupling allows the plumbing contractor to:

- Rotate each clamp independently around the gasket in order to facilitate easy assembly.

- Apply either side of a coupling to a pipe or a fitting and to completely tighten to 60 inch-lbs without affecting the opposite side of the coupling.

- Complete a joint in a fraction of the time of traditional couplings.

- Make a tight, permanent seal.



RIGID QUIK

Code #	Size/Description
6010	1-1/2 CI, Plastic-1-1/4 Copper
6011	1-1/2 CI, Plastic-1 1/2 CI Plastic
6012	1-1/2 CI, Plastic-1 1/2 Copper, 1 1/4 Plastic
6020	2 CI, Plastic - 1 1/4 Copper
6021	2 CI, Plastic - 1 1/2 CI Plastic
6022	2 CI, Plastic - 1 1/2 Copper, 1 1/4 Plastic
6023	2 CI, Plastic - 2 CI, Plastic
6024	2 CI, Plastic - 2 Copper
6030	3 CI, Plastic - 1 1/4 Copper
6031	3 CI, Plastic - 1 1/2 CI, Plastic
6032	3 CI, Plastic - 1 1/2 Copper, 1 1/4 Plastic
6033	3 CI, Plastic - 2 CI, Plastic
6034	3 CI, Plastic - 2 Copper
6035	3 CI, Plastic - 3 CI, Plastic
6036	3 CI, Plastic - 3 Copper
6040	4 CI, Plastic - 2 CI, Plastic
6041	4 CI, Plastic - 3 CI, Plastic
6042	4 CI, Plastic - 3 Copper
6043	4 CI, Plastic - 4 CI, Plastic