



anaco-husky

ANACO FAMILY OF COUPLINGS



anaco



Anaco is the largest manufacturer of couplings in the United States providing the perfect solution for joining hub-less cast iron pipe and fittings in drainage, waste and vent (DWV) plumbing systems as well as dissimilar piping products—a **complete coupling solution**.

PRODUCTS

- Anaco No-Hub Coupling
- Cremco Transition Coupling
 - Shielded Transition Coupling
 - Unshielded Flex Coupling
 - ARC Shielded Coupling
- Rigid Quik Coupling
- Service Weight Gaskets
- Husky CR 7000 Coupling
 - 316- SS Corrosion Resistance
- Husky SD 4000 Coupling
- Husky HD 2000 Coupling
- Husky Transition Couplings
 - SD 4200—PVC x Cast Iron
 - SD 4100—Copper x Cast Iron
 - SD 4000—Cast Iron Reducers



HUSKY SD 4000 COUPLINGS

Husky SD 4000 Couplings have been engineered by Anaco to provide a heavy-duty, all stainless steel coupling, balancing the desire for a more rigid joint with the need to provide a superior positive seal, which can accommodate possible disparities in the No-Hub pipe and fittings. This has been accomplished by manufacturing our coupling with a super-duty corrugated shield of sufficient width to accommodate additional surface-bearing sealing clamps.

Size	Width	# Straps	Torque
1½" to 4"	3.0	4	80
5" & 6"	4.0	6	80
8" & 10"	4.0	6	80
12" & 15"	5.5	6	80

PRODUCTS

- Husky SD 4000
- Husky SD 4200 Transition
 - PVC x CI 1½"–10"
- Husky SD 4000 Reducer
 - 2" x 1½", 3" x 2", 4" x 3", 4" x 2"
- Husky SD 4100 Transition
 - CI x Copper 2" x 1½", 2" x 2"

CERTIFICATIONS & STANDARDS

Tested & Certified to:

- ASTM C 1540
 - 4200 Meets ASTM C 1460
- ASTM C 564
- FM 1680 Class 1
- CSA B 602
- IAPMO File 6726
 - 4200 IAPMO File 5794
- 100% made in the USA
- Compliant to BAA, TAA, ARRA and NAFTA

APPLICATIONS

- | | | | |
|----------------|-----------------|---------------------|----------------------|
| ■ HOSPITALS | ■ STORM SYSTEMS | ■ CORRECTIONAL | ■ AIRPORTS |
| ■ UNIVERSITIES | ■ SEISMIC AREAS | ■ DATA CENTERS/LABS | ■ CONVENTION CENTERS |
| ■ MUSEUMS | ■ GOVERNMENT | ■ SPORTS STADIUMS | ■ HIGH RISES |



HUSKY CR 7000 316 STAINLESS STEEL

The Husky CR 7000 Corrosion Resistant Coupling is the first 316 stainless steel, heavy-duty coupling. It balances the desire for a more rigid joint with the need to provide a superior positive seal, which can accommodate possible disparities in the no-hub pipe & fittings. Sizes: 1½"–10"

APPLICATIONS

- CORROSIVE ENVIRONMENTS
- AROUND WATERWAYS
- EXPOSED AREAS
- PARKING GARAGES
- BRIDGES/TUNNELS
- UNDERGROUND

CERTIFICATIONS & STANDARDS

Tested & Certified to:

- ASTM C 1540
- ASTM C 564
- FM 1680 Class 1
- IAPMO File 6726
- 100% made in the USA

HUSKY HD 2000 COUPLINGS



Husky HD 2000 Couplings have a slightly thinner shield than the Husky SD 4000. They consist of a 304 stainless steel shield, clamp assembly and a neoprene gasket. The 305 stainless steel 5/16" screw requires 80-inch pounds of torque. Sizes: 1½"–10"

APPLICATIONS

- HOTELS
- MUNICIPAL
- CASINOS
- COMMERCIAL
- INDUSTRIAL
- OFFICES

CERTIFICATIONS & STANDARDS

Tested & Certified to:

- ASTM C 1540
- ASTM C 564
- FM 1680 Class 1
- CSA B 602
- IAPMO File 6726
- 100% made in the USA
- Compliant to BAA, TAA, ARRA and NAFTA



anaco STANDARD NO-HUB COUPLINGS

CERTIFICATIONS & STANDARDS

Tested & Certified to:

- CISPI 310
- ASTM C 1277
- ASTM C 564
- NSF™ Certified
- IAPMO File 2206
- 100% made in the USA
- Compliant to BAA, TAA, ARRA and NAFTA

Anaco No-Hub couplings consist of a 300 Series stainless steel shield, clamp assembly and a Neoprene gasket. Coupling sizes range from 1½" through 15" diameters.



TRANSITION COUPLINGS

PRODUCTS

- **Cremco Specialty Transition Couplings**
 - Shielded Transition Coupling
 - Unshielded Flex Coupling
 - ARC Shielded Coupling
- **Rigid Quik Unshielded Couplings** – Meets ASTM 1461

FEATURES

- Meets and exceeds material and performance requirements of ASTM C 1460
- Neoprene gaskets meet and exceed ASTM C564
- Neoprene gaskets integrate transitional design with center stop serving as noise dampening mechanism
- All 300-series stainless steel components meet ASTM A240



SERVICE WEIGHT GASKETS

PRODUCTS

- Ty-Seal
- EZ-Tight

FEATURES

- Available in sizes from 2"–15"
- Neoprene rubber meets/exceeds ASTM C564
- 100% made in the USA